

HOME DISTRIBUTION ENCLOSURES



Fully featured enclosures

- Suitable for mounting internally
- 4mm diameter bursts for easy mounting of DIN Rail
- Industry standard hole patten for flexible third party equipment
- Space for additional port patch units
- Hinged mounting pan allows easy access behind mount pan to route fibre to NTD enclosure
- Supplied with double GPO compliant with AS/NZS3000
- Cable entries provide pre-punched knockouts for easy cable access
- Mounting position for NBN battery backup power supply
- Mounting position with screws for standard NBN NTD enclosure
- Supplied with one 8-port patch unit (on selected models only)
- Available with window front door or full steel door option
- Optional flush kit available (NBN-HDCFK2)



Basic enclosures

- Suitable for mounting internally
- 4mm diameter bursts for easy mounting of DIN Rail
- Industry standard hole patten for flexible third party equipment
- Space for additional port patch units
- Cable entries provide pre-punched knockouts for easy cable access
- Mounting position for NBN battery backup power supply
- Mounting position with screws for standard NBN NTD enclosure
- Available with window front door
- Optional flush kit available (NBN-HDCFK2)

HOME DISTRIBUTION ENCLOSURES



ORDERING GUIDE

Part Number	Inclusions			Dimensions (mm)			Window Opening (mm)	
	GPO	Patch panel	Door Type	Height	Width	Depth	Height	Width
NBN-HDC01			Window	650	380	120	597	320
NBN-HDC10	•	•	Window	650	380	130	520	255
NBN-HDC13	•		Window	650	380	130	520	255
NBN-HDC02			Window	1000	380	120	947	320
NBN-HDC20	•	•	Window	1000	380	130	852	255
NBN-HDC23	•		Window	1000	380	130	852	255
NBN-HDC15	•	•	Metal	650	380	130	-	-
NBN-HDC17	•		Metal	650	380	130	-	-
NBN-HDC25	•	•	Metal	1000	380	130	-	-
NBN-HDC27	•		Metal	1000	380	130	-	-

Please Note: Window door option Wi-Fi ready

FEATURES COMPARISON

Features	Basic	Fully featured
Suitable for mounting internally	✓	✓
4mm diameter bursts for easy mounting of DIN Rail	✓	✓
Industry standard hole patten for flexible third party equipment	✓	✓
Space for additional port patch units	✓	✓
Hinged mounting pan allows easy access behind mount pan to route fibre to NTD enclosure.		✓
Supplied with double GPO compliant with AS/NZS3000		✓
Cable entries provide pre-punched knockouts for easy cable access	✓	✓
Mounting position for NBN battery backup power supply	✓	✓
Mounting position with screws for standard NBN NTD enclosure fitting	✓	✓
Supplied with one 8-port patch unit (on selected models only)		✓
Window option for Wi-Fi signal transmission	✓	✓
Optional flush kit available (NBN-HDCFK2)	✓	✓