

374CUR2-C & 374CUI2-C - TELECOM SPLICE CONNECTORS – 2 WAY AND 3 WAY

INTRODUCING CABAC CERTIFIED COMMUNICATION CONNECTORS & TOOLS.

CABAC Telecom Splice Connectors are specifically designed to quickly connect two or three telecom conductors. Simply insert the un-stripped wires, and crimp the cap of the connector using a CABAC TELSP2 tool, and the wires are connected forever.

- CABAC Telecom Splice connectors are certified to AS S008:2010
- CABAC Telecom Splice connectors comply with ACMA requirements for use in Telecommunications applications as Supplier E1508
- Contact pins are tin plated brass
- Connectors are filled with dimethylsilicone fluid insulation.
- Bodies are made from polycarbonate plastic that resists splitting, rough handling and solvents.

The connection method is Insulation Displacement Connection (IDC), which is proven to be the most stable in the long term. Two IDC elements are used in each connection for greater joint integrity. Ensure any crimp tool used has a parallel action, like the CABAC TELSP2 tool which is recommended for this application.

Technical Data

Cable style and wire diameter (mm):

Max insulation diameter (mm):	2.08
Full plastic (unfilling):	0.4-0.9
Full plastic (filling):	0.4-0.9
Conductor sizes	26-19 AWG

Mechanical Performance

Plastic Housing:	PC (UL 94v-0)
Contacts:	Phosphor Bronze
Wire Insertion Force:	45N Typical
Wire Pull out Force:	40N Typical
Use Times:	>100

Environment Characteristics

Storage Temperature Range:	-40 °C ~ +120 °C
Operating Temperature Range:	-30 °C ~ +70 °C
Relative Humidity:	<95% (at 20 °C)
Atmospheric Pressure:	70KPa ~106KPa

Electrical Performance

Insulation Resistance:	$R \geq 1000M \text{ Ohm}$
Contact Resistance:	$R \leq 5m \text{ ohm}$
Dielectric Strength:	1200V DC 60s can't spark over and do not have fly arc
Constant Current:	5KA 8/20u Sec
Surge Current:	10KA 8/20u Sec
2 Wire (Colour: Red)	374CUI2-C
3 Wire (Colour: Yellow)	374CUR2-C



374CUR2-C (3 Wire)



374CUI2-C (2 Wire)



TELSP2

ORDERING INFORMATION

Part No.	No. of Conductors	Pack Qty
374CUI2-C	2	100
374CUR2-C	3	100

TELSP2 TELECOMMUNICATIONS
SPLICE CRIMPER

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.

AU T: 133 122 | F: 1300 303 310 | E: sales@cabac.com.au | W: cabac.com.au

NZ T: 0800 77 69 69 | F: 0800 88 69 69 | E: sales@cabac.co.nz | W: cabac.co.nz