

RUSH



1652301 • Clear Lens



1652302 • Smoke Lens



1652310 • Twilight Lens



24 g

- + ULTRA LIGHT WEIGHT**
- + BUILT IN BROW PROTECTION**
- + FULLY RECYCLABLE ALL POLYCARBONATE FRAME**
- + ADJUSTABLE PVC NOSE BRIDGE PLUS COMFORT BARS IN THE TEMPLE ARMS.**

bolle
SAFETY

RUSH

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
RUSH	 Clear	1652301	IO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Smoke	1652302	I3	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Twilight	1652310	I1	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog

LENS MARKING

- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% (clear).
- 1. Range of luminous transmittance 43 -88% (twilight).
- 3. Range of luminous transmittance 8 -18% (smoke).

APPLICATIONS

- Assembly and production work
- Process work
- Emergency response
- Driving
- Solar UV exposure
- Laboratory
- Dental

MAIN MARKETS

- Manufacturing
- Petrochemical
- Construction
- Government
- Mining
- Medical and dental
- Food industry

LENSES

- 2mm polycarbonate
- 9 base curve
- 'ALS' anti-fog/anti-scratch coating on both sides of lens: Clear, Smoke and Twilight
- 100% UV 385 – Clear
- 100% UV 400 – Smoke, Twilight

CLEANING AND STORAGE

CLEANING : Bollé Safety recommends only using our **CLEAN** Lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS

LENSES	PC - 2,2 mm - Curve 9
FRAME	PC + PVC
STRAP	Non Applicable
FOAM	Non Applicable
SPARE LENSES	No

FRAME MARKING

AS/NZS 1337.1.2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

ASIA/PACIFIC HEADQUARTERS :

Bollé Australia Pty Ltd
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: safety@bolle.com.au

NEW ZEALAND:

Bollé New Zealand Limited
Unit 5, 114 Sawyers Arms Road
Papanui, Christchurch 8052
T: 03 3751400
E: bolle@bolle.co.nz