



WBMDUPB

## Mechanism push dimmer trailing-edge

### Technical characteristics

#### Main electrical features

Nominal voltage	230 V
Frequency	50 Hz

#### Voltage

Operating voltage	230 V~ +10%/-15%
-------------------	------------------

#### Fuse

Fuse	short-circuit and overload proof (electronic fuse)
------	--

#### Dimensions

Depth	51 mm
Height	24 mm
Width	24 mm

#### Power

Power consumption (standby)	max. 0.1 W
Electronic transformers	20...350 W

#### Measurement

Extension unit input	with extension unit input for slave push-button WBMSLL
----------------------	---

#### Materials

Colour	white
Material	Polycarbonate (PC)

#### LED control

Dimmable 230 V LED lamps	2.5...250 W
LED	with blue status LED

#### Incandescent bulbs control

230 V incandescent lamps and halogen lamps	7...300 W
--	-----------

#### Installation, mounting

Installation mode	RotoLoc ®
-------------------	-----------

#### Connection

Conductor cross-section	1.5 mm²
-------------------------	---------

#### Cable

Cable length, extensions	max. 20 m
--------------------------	-----------

**Equipment**

On/Off switch	Yes
Dimming principle	phase cut-off
Brightness	with brightness memory

**Use conditions**

Operating temperature	-5...50 °C
Storage/transport temperature	-20...70 °C
Temperature	with overheating protection

**Identification**

Main design line	Mechanisms
meta_keyword	Dimmer;Switch;Regulator;Controller;Rheostat;