



255



415VF



765



265/1



265/5



265/7D

MOUNTING ENCLOSURES

The 255 Weatherproof Mounting Enclosure Boxes convert standard range flush switches and switch sockets into Weatherprotected equivalents for permanent exterior use. Clipsal 255 Series moulded boxes are all insulated and do not require earthing. A clear impact resistant padlockable flap is provided to prevent unauthorised use of the enclosed accessory. Boxes can be surface mounted or semi-recessed. A special rigid P.V.C. surround (255Z) is available for use where boxes are semi-recessed into finished brickwork. Installation of the 255 Series can be completed by back wiring and surface wired through 20mm and 25mm screwed conduit entries in the top or bottom of box. Back wire through rear entry cutouts. Spare insulated plugs are provided with each box to seal entries not in use. Washers are supplied in both entries to ensure perfect sealing. The Catalogue Number 225 provides similar protection to architrave outlets and intermediate switch plates. Mines and Energy South Australia Approval S/1. Standard colours are Grey & White.

225	Rigid P.V.C. Weatherprotected Shroud. Suits Clipsal 16 Switched Socket and No.s 31BA and 32BA Switches. Also suits Flush Plates up to 99 x 49mm with either 55mm or 78mm mounting centres
255	Rigid P.V.C. Weatherprotected Enclosure with clear flap. Suits Flush Plates 115 x 73mm with 84mm mounting centres
255Z	Rigid P.V.C. Enclosure Surround for recessing box in brickwork. Overall size 150 x 107mm
223H	Rigid Weatherprotected Shroud suits Standard Range and 2000 Series

CARAVAN INLET AND OUTLET RANGE

The new inlet and outlet range comes with an IP34 rating and is available in the standard colours white and black. Overall dimension is 101 x 80 x 38mm.

Cat. No.	Description	IP Rating
435VFS15	250V 15A Caravan Inlet	34
415VF15	250V 15A Caravan Outlet	34
415VF	250V 10A Caravan Outlet	34
435VFSM	Mounting Flange	NA
435VFS15FLAP	Flap to suit 435VFS15	NA
415VFFLAP	Flap to suit 415VF	NA

ADAPTABLE ENCLOSURES

These adaptable enclosures have an International Protection Rating of IP56 when suitable silicon sealant is used. (Acid Cure Silicon Sealants recommended). Supplied complete with P.V.C. mounting panel incorporating earth terminal. Standard colour Grey. For details of Industrial adaptable enclosures see the '56 Series Industrial Range Technical Manual'.

763	Adaptable Enclosure with rigid P.V.C. Box. Deep transparent cover and sealing gasket	
	Overall dimensions	108 x 108 x 139mm
	Internal dimensions	92 x 92 x 117mm
764	Adaptable Enclosure with rigid P.V.C. Box. Deep transparent cover and sealing gasket	
	Overall dimensions	163 x 108 x 142mm
	Internal dimensions	142 x 92 x 122mm
765	Adaptable Enclosure with rigid P.V.C. Box. Deep transparent cover and sealing gasket	
	Overall dimensions	211 x 108 x 139mm
	Internal dimensions	195 x 92 x 117mm

RIGID P.V.C. ADAPTABLE BOXES

These adaptable boxes are rated IP56 when suitable silicon sealant is used. (Acid Cure Silicon Sealants recommended). Standard colour Grey.

Cat. No.	Overall Dimensions mm		
	Length	Width	Height
265/1	77	77	54
265/3	108	108	76
265/4	163	108	81
265/5	211	108	81
265/7	300	200	152
265/7D	300	200	200
265/7D,TR	300	200	200
763	108	108	139
764	163	108	142
765	211	108	139

265/1	Rigid P.V.C. Adaptable Box. Supplied with sealing gasket	Internal dimensions 70 x 70 x 43mm
265/3	Rigid P.V.C. Adaptable Box. Supplied with sealing gasket	Internal dimensions 96 x 96 x 64mm
265/4	Rigid P.V.C. Adaptable Box. Supplied with sealing gasket	Internal dimensions 140 x 95 x 68mm
265/5	Rigid P.V.C. Adaptable Box. Supplied with sealing gasket	Internal dimensions 196 x 95 x 68mm
265/7	Rigid P.V.C. Adaptable Box. Supplied with sealing gasket	Internal dimensions 276 x 176 x 133mm
265/7,TR	Rigid P.V.C. Adaptable Box with clear lid. Supplied with sealing gasket.	Internal dimensions 276 x 176 x 133mm
265/7D	Deep rigid P.V.C. Adaptable Box with sealing gasket	Internal dimensions 276 x 176 x 183mm

265GT1	Sealing Gasket. Suits 265/1 Box.	77 x 77 x 3mm
265GT3	Sealing Gasket. Suits 265/3 and 763 Boxes.	108 x 108 x 3mm
265GT4	Sealing Gasket. Suits 265/4 and 764 Boxes.	163 x 108 x 3mm
265GT5	Sealing Gasket. Suits 265/5, 252/63 and 765 Boxes.	211 x 108 x 3mm
265GT7	Sealing Gasket. Suits 265/7 and 265/7D Boxes.	300 x 200 x 3mm