

## INSULATED SCREW CONNECTORS

CABAC heavy duty Insulated Screw Connectors accommodate a maximum of 2 x 6mm<sup>2</sup> cables and are made into one and two screw formats. The wire protector version and two screw insulated connectors can be used for earth/neutral connections. The wire protector covers more than 80% of the connection tunnel as prescribed in AS3000 2018 clauses 2.10.4.2 or 3.7.2.9.2.

They are typically used by electricians, in junction boxes for general connections, to connect light fittings, and virtually anywhere in general purpose wiring.

### FEATURES AND BENEFITS

- They have a clear plastic housing so that the termination can be visually checked
- Nominal 32A rating, dependant on conductor loading
- Rated for normal 240/415V applications
- Connectors are supplied in handy screw top jars

### TECHNICAL DATA

MATERIAL	DESCRIPTION
Body	Polycarbonate (No Halogen)
Connections	Brass
NOMINAL RATINGS	DESCRIPTION
Voltage	240/415V
Amperage	32A

### COMPLIANCE AND SAFETY

- AS/NZS IEC 60998.2.1 2002
- AS/NZS 3100.2017
- RoHs

### ORDERING INFORMATION

PART NO.	DESCRIPTION	JAR QTY	JAR WEIGHT
C32A1	Single Screw Connector 32A	100	330g
C32A1-P	Single Screw Connector with wire protector plate 32A	100	345g
C32A2	Double Screw Connector 32A	50	330g



C32A1



C32A1-P



C32A2

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.