





HSI-T METALARC




- Single ended quartz metal halide lamps with a compact tubular clear outer envelope
- Small point light source allows compact luminaire designs
- Ideal for spotlighting where high intensities are required
- UV-stop outer jacket for reduced risks of fading
- Suitable for interior accent and display lighting
- Exterior applications in floodlighting of monuments, parks and facades
- Average lamp life: 9000 hours



Metal Halide HSI-T/WDL



Metal Halide HSI-T/NDL



HSI-T METALARC

Code	Description	Watt	Volt	Current	Cap	Lamp Finish	Colour Temp	CRI Group	Luminous Flux	Packing Qty.
HSI-T MetalArc										
203340	HSI-T 35W/WDL	37W	90V	0.53A	G12	Clear	3000K	2B	3000 lm	12
203400	HSI-T 35W/NDL	37W	90V	0.53A	G12	Clear	4200K	2A	3100 lm	12
203350	HSI-T 70W/WDL	75W	95V	0.95A	G12	Clear	3000K	2B	5200 lm	12
203410	HSI-T 70W/NDL	75W	95V	0.95A	G12	Clear	4200K	2B	5500 lm	12
203355	HSI-T 100W/WDL	100W	100V	0.95A	G12	Clear	3000K	2B	8000 lm	12
203415	HSI-T 100W/NDL	100W	100V	0.95A	G12	Clear	4200K	2B	8400 lm	12
203360	HSI-T 150W/WDL	146W	95V	1.82A	G12	Clear	3000K	2B	12000 lm	12
203420	HSI-T 150W/NDL	146W	95V	1.82A	G12	Clear	4200K	2B	12500 lm	12
203350S	HSI-T 70W/WDL-Short	75W	95V	0.95A	G12	Clear	3000K	1B	5300 lm	12
203410A	HSI-T 70W/NDL-Short	75W	95V	0.95A	G12	Clear	4200K	1B	5800 lm	12
203360S	HSI-T 150W/WDL-Short	146W	95V	1.82A	G12	Clear	3000K	1B	13000 lm	12
203420A	HSI-T 150W/NDL-Short	146W	95V	1.82A	G12	Clear	3000K	1B	12900 lm	12