

Residual current circuit breaker (RCCB), 63A, 4p, 30mA, type G/A



Part no. PFIM-63/4/003-G/A-MW
235457
EL Number 1609338
(Norway)

General specifications

Product name	Eaton Moeller series xPole - PFIM Type AC, A, U, R RCCB
Part no.	PFIM-63/4/003-G/A-MW
EAN	4015082354572
Product Length/Depth	80 millimetre
Product height	76 millimetre
Product width	70 millimetre
Product weight	0.384 kilogram
Compliances	RoHS conform
Certifications	IEC/EN 61008 ÖVE E 8601
Product Tradename	xPole - PFIM Type AC, A, U, R
Product Type	RCCB
Product Sub Type	None

Delivery program

Application	3-phase application without N (400V AC phase-phase) not allowed Residual current circuit breaker for residential and commercial applications xPole - Switchgear for residential and commercial applications
Number of poles	Four-pole
Tripping time	Short time-delayed
Amperage Rating	63 A
Rated short-circuit strength	10 kA
Fault current rating	30 mA
Sensitivity type	Pulse-current sensitive
Impulse withstand current	Surge-proof, 3 kA
Type	PFIM Residual current circuit breakers Type G/A (ÖVE E 8601)

Technical Data - Electrical

Voltage rating	230 V AC / 400 V AC
Rated operational voltage (Ue) - max	400 V
Rated insulation voltage (Ui)	440 V
Rated impulse withstand voltage (Uimp)	4 kV
Rated fault current - min	0.03 A
Rated fault current - max	0.03 A
Frequency rating	50 Hz
Short-circuit rating	63 A (max. admissible back-up fuse)
Leakage current type	A
Rated residual making and breaking capacity	630 A
Admissible back-up fuse overload - max	40 A gG/gL
Rated short-time withstand current (Icw)	10 kA
Surge current capacity	3 kA
Test circuit range	196 V AC - 264 V AC
Pollution degree	2
Lifespan, electrical	4000 operations

Technical Data - Mechanical

Frame	45 mm
Width in number of modular spacings	4
Built-in width (number of units)	70 mm (4 SU)

Built-in depth		70.5 mm
Mounting Method		Quick attachment with 2 latch positions for DIN-rail IEC/EN 60715 DIN rail
Degree of protection		IP20, IP40 with suitable enclosure IP20
Terminals (top and bottom)		Open mouthed/lift terminals
Terminal capacity (solid wire)		1.5 mm ² - 35 mm ²
Connectable conductor cross section (solid-core) - min		1.5 mm ²
Connectable conductor cross section (solid-core) - max		35 mm ²
Terminal capacity (stranded cable)		16 mm ² (2x)
Connectable conductor cross section (multi-wired) - min		1.5 mm ²
Connectable conductor cross section (multi-wired) - max		16 mm ²
Terminal protection		Finger and hand touch safe, DGUV VS3, EN 50274
Busbar material thickness		0.8 mm - 2 mm
Lifespan, mechanical		20000 operations
Permitted storage and transport temperature - min		-35 °C
Permitted storage and transport temperature - max		60 °C
Climatic proofing		25-55 °C / 90-95% relative humidity according to IEC 60068-2
Design verification as per IEC/EN 61439 - technical data		
Rated operational current for specified heat dissipation (In)		63 A
Heat dissipation per pole, current-dependent		0 W
Equipment heat dissipation, current-dependent		13.4 W
Static heat dissipation, non-current-dependent		0 W
Heat dissipation capacity		0 W
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		60 °C
Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
Additional information		
Accessories required		Z-HK 248432
Features		Residual current circuit breaker Additional equipment possible
Fitted with:		Interlocking device
Functions		Short-time delayed tripping

Special features			Maximum operating temperature is 60 °C: Starting at 40 °C, the max. permissible continuous current decreases by 1.8% for every 1 °C Tripping signal contact for subsequent installation Z-NHK 248434
Used with			PFIM Residual current circuit breakers Type G/A (ÖVE E 8601) KLV-TC-4 276241 (Compact enclosure) Z-FW/LP 248296 (Remote control and automatic switching device) Z-RC/AK-4MU 101062 (sealing cover set)

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / Residual current circuit breaker (RCCB) (EC000003)			
Electric engineering, automation, process control engineering / Electrical installation, device / Residual current protection system / Residual current circuit breaker (RCCB) (ecI@ss13-27-14-22-01 [AAB906019])			
Number of poles			4
Rated voltage		V	400
Rated current		A	63
Rated fault current		A	0.03
Rated insulation voltage Ui		V	440
Rated impulse withstand voltage Uimp		kV	4
Power loss		W	
Mounting method			DIN rail
Leakage current type			A
Selective protection			No
Short-time delayed tripping			Yes
Short-circuit breaking capacity (Icw)		kA	10
Surge current capacity		kA	3
Voltage type			AC
With interlocking device			Yes
Frequency			50 Hz
Additional equipment possible			Yes
Degree of protection (IP)			IP20
Width in number of modular spacings			4
Built-in depth		mm	70.5
Ambient temperature during operating		°C	-25 - 60
Pollution degree			2
Connectable conductor cross section multi-wired		mm ²	1.5 - 16
Connectable conductor cross section solid-core		mm ²	1.5 - 35
RAL-number (similar)			7035
Explosion-proof			No