



SmartBright Floodlight G2 BVP151

BVP151 LED60/NW PSU 50W SWB G2 GM

SmartBright Floodlight G2 BVP151, 6000 lumen, 50 W, 840 neutral white, Safety class I

The SmartBright G2 LED Floodlight features best-in-class technology to deliver high lumen efficacy with a long lifetime and reliable design. The symmetrical optical distribution improves the light effect. The product is an ideal solution for most floodlight applications.

Product data

General Information			
Driver included	Yes	Inrush current	1.68 A
Lighting Technology	LED	Power Consumption	50 W
CE mark	-	Power Factor (Fraction)	0.95
Flammability mark	-	Connection	Flying leads/wires
		Cable	Cable 1.0 m without plug 3-pole
		Number of products on MCB of 16 A type B	44
Light Technical		Temperature	
Luminous Flux	6,000 lumen	Ambient temperature range	-25 to +40 °C
Correlated Color Temperature (Nom)	4000 K		
Luminous Efficacy (rated) (Nom)	120 lm/W	Controls and Dimming	
Color rendering index (CRI)	>80	Dimmable	No
Light source color	840 neutral white	Control interface	-
Optical cover type	Glass		
Operating and Electrical		Mechanical and Housing	
Input Voltage	220-240 V	Housing Material	Aluminum die-cast
Line Frequency	50 or 60 Hz	Optical cover material	Tempered glass

