



Main

| | |
|-------------------------------------|---|
| Range | Acti 9 |
| Product name | Acti 9 iID |
| Product or component type | Residual current circuit breaker (RCCB) |
| Device short name | iID |
| Poles description | 4P |
| Neutral position | Left |
| [In] rated current | 40 A |
| Network type | AC |
| Earth-leakage sensitivity | 30 mA |
| Earth-leakage protection time delay | Instantaneous |
| Earth-leakage protection class | Type A |

Complementary

| | |
|---|--|
| Device location in system | Outgoer |
| Network frequency | 50/60 Hz |
| [Ue] rated operational voltage | 380...415 V AC 50/60 Hz |
| Residual current tripping technology | Voltage independent |
| Rated breaking and making capacity | Im 1500 A Idm 1500 A |
| Rated conditional short-circuit current | 10 kA |
| [Ui] rated insulation voltage | 500 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 6 kV |
| Contact position indicator | Yes |
| Control type | Toggle |
| Local signalling | Trip indicator |
| Mounting mode | Clip-on |
| Mounting support | DIN rail |
| 9 mm pitches | 8 |
| Height | 91 mm |
| Width | 72 mm |
| Depth | 73.5 mm |
| Product weight | 0.37 kg |
| Colour | White |
| Mechanical durability | 20000 cycles |
| Electrical durability | 15000 cycles AC-1 |
| Locking options description | Padlocking device |
| Connections - terminals | Single terminal, top or bottom rigid wire(s) 1...35 mm ² max Single terminal, top or bottom flexible wire(s) 1...25 mm ² max Single terminal, top or bottom flexible with ferrule wire(s) 1...25 mm ² max |
| Wire stripping length | 14 mm (top or bottom) |
| Tightening torque | 3.5 N.m (top or bottom) |

Environment

| | |
|-------------------------|--|
| standards | EN/IEC 61008-1 |
| IP degree of protection | IP20 conforming to IEC 60529 IP40 for modular enclosure conforming to IEC 60529 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|---------------------------------------|---|
| pollution degree | 3 |
| electromagnetic compatibility | 8/20 µs impulse withstand, 250 A conforming to EN/IEC 61008-1 |
| ambient air temperature for operation | -25...60 °C |
| ambient air temperature for storage | -40...85 °C |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0627 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |