



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	User manual
Max runtime	240 min
Number of tare power	20 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS

Physical

Cable length	1.22 m
Colour	Black
Depth	39 cm
Height	19 cm
Mounting preference	No preference
Net weight	10.3 kg
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No
Width	14 cm

Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Plug standard	IEC 60320 C14
Input voltage limits	140...300 V
Number of cables	1
Input voltage	230 V

Cos phi	0.56
---------	------

Output

Rated power in W	900 W
Maximum configurable power in W	900 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Nb of power socket outlets	4 Australian
Curve equation	Efficiency
Curve fixed loss	0.0206
Curve load maximum	100 %
Curve load minimum	3 %
Curve proportional loss	0
Curve square loss	0.0106
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 230V/50Hz electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Full load runtime	00:01:00 900 W
Graph display	1
Half load runtime	00:06:30 450 W
Output voltage	230 V
Maximum configurable power in VA	1600 VA
Rated power in VA	1600 VA
Transfer time	6 ms typical : 10 ms maximum

Conformance

Product certifications	CE CB RCM
Standards	EN/IEC 62040-1 EN/IEC 62040-2 CE
Equipment protection policy	Lifetime : 50000 euros

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	Non-condensing 0...95 %
Storage altitude	0...3000 m
Acoustic level	40 dBA
Show note OP temperature	No
IP degree of protection	IP20

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Liquid value	0
Battery curve	C
Battery power in VAH	136 VAh runtime 168 VAh capacity
Battery life	3...5 year(s)
Battery graph comments	Curve fit to measured runtime data. All measurements taken with new, fully charged batteries, at typical environmental conditions, with no electrical input and balanced resistive load (PF = 1.0) output.
Extended runtime	0

Communications & Management

Control panel	LED Status display with on line : on battery
Alarm	Alarm when on battery : distinctive low battery alarm

Surge Protection and Filtering

Surge energy rate	273 J
Data line protection	RJ45 10/100/1000 Base-T Ethernet protection

Packing Units

Package 1 Weight	11.3 kg
Package 1 Height	29.7 cm
Package 1 width	23.5 cm
Package 1 Length	49.5 cm
SCC14	10731304410772

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------