



**A.B.N.: 38 008 091 825**

*Williams Mining & Industrial Sales Pty Ltd  
Australia's Leading Metal Conduit Specialists*

28 Burwood Ave,  
Woodville North,  
S.A. 5012.

Tel: 08 82685477  
Fax: 08 82685433

Email: [Info@williamsmining.com.au](mailto:Info@williamsmining.com.au)

## **DATA SHEET**

### **WMI-C3-A Conduit to AS2053.7. Galv/to AS1397**

WMIS Australian made conduit is manufactured from BHP Mild Steel Galvabond tube. It has an accurate circular cross section, a uniform wall thickness and continuously welded seams. The interior and exterior surfaces are thoroughly and evenly coated via the inline process

The conduit is manufactured to 4 meter lengths, is threaded both ends and includes one coupling per length as is the requirement of AS/NZ 2053.7 Thread Pitch is 1.5mm.

Storage: It is highly recommended that Steel conduit be stored in a dry area until required.

Application: WMIS-C3 conduit can be installed indoors, in dry locations, exposed or concealed, in all kinds of atmospheric conditions, and in hazardous locations. It provides excellent mechanical protection for the conductors while reducing Electro-Magnetic field exposure and shielding against Electro-Magnetic Interference.

#### Conduit Dimensions:

Size: mm	Part No:	Length:	Wall Thickness	Thread Pitch	HDG coupling	Outside diameter	Internal diameter
20	WMI-20C3	4M	1.6mm	1.5	supplied	20mm	16.8mm
25	WMI-25C3	4M	1.8mm	1.5	supplied	25mm	21.4mm
32	WMI-32C3	4M	1.8mm	1.5	supplied	32mm	28.4mm
40	WMI-40C3	4M	1.8mm	1.5	supplied	40mm	36.4mm
50	WMI-50C3	4M	2.0mm	1.5	supplied	50mm	46.0mm

*Country of origin & Manufacture: Australia*