


SERVICE FUSE FITTINGS & LINKS - TYPE 2A

Features:

- ✓ Standards: AS60269.
- ✓ Rated Voltage: 500V.
- ✓ Max. cable size 35mm².

Applications:

- ✓ Fault current limitation.
- ✓ Off-load isolation.
- ✓ Domestic service installations.



Fuse Size	Current Rating (A)	Type	Pack Qty	Part No.
2A Fittings - Black				
2A 22 x 57	100	Back wire service fuse fitting	10	S71002ABWS
		Front wire service fuse fitting		S71002AFWS

125A Service disconnect (Queensland)

2A 22 x 57	125	Back wired off-load service disconnect Clear body with 4 entries. Link fitted.	10	S7125BWQ
2A 22 x 57	125	Front wired off-load service disconnect Clear body with 4 entries. Link fitted.	10	S7125FWQ

*Nylon fixing screw & nut included.

Hardware

Mounting Screw, Plastic M5x40 (Order 1 = One pack of 100 pieces)	1	S7SCREW
Mounting Nut, Plastic M5 (Order 1 = One pack of 100 pieces)	1	S7NUT

2A Fuse Links

2A 22 x 57	20	10	22G20
	30		RHF30
	40		RHF40
	45		RHF45
	50		RHF50
	60		RHF60
	80		RHF80
	100		RHB100

Metering Link - sealable

n/a	100	Neutral link for Victorian single phase meter Panels, enclosed. (69mmH x 82mmW x 56mmD)	10	VICLINK
n/a	100	Neutral link for NSW single phase meter Panels, enclosed. (69mmH x 82mmW x 56mmD)	10	NSWLINK

FUSED METER PANEL

Volatge Rating (V)	Current Rating (A)	Description	Pack Qty	Part No.
2A Type fitting				
500	100	single phase meter panel c/w series 7 fitting	10	DMP7
		three phase meter panel c/w series 7 fittings		DMP8