

RJ6U24PPC

Clipsal Patch Panel Flat 19" 1U 24-port Keystone
UTP Loaded Cat6 Non-shutter



Main

Range	Actassi
Product brand	Clipsal
Product or component type	Patch panel
Device application	Punch down tool Quick termination tool
Device presentation	Complete product
Colour	Grey RAL 7040
Colour code	TIA-568A/B
Quantity per set	Set of 1

Complementary

Type of footprint	S-110 keystone
[In] rated current	1.5 A 25 °C
AWG gauge	AWG 24...AWG 23
Cable outer diameter	0.9...1.4 mm
Cable shielding type	U/UTP
Communication network category	6
Provided equipment	Removable cable tray 1 Removable cable tray 1 Label holder 3 inside the rack Ports identification at the rear 24 With RJ45 connectors 24 Side cover 2 6 U/UTP inside the enclosure
Number of rack unit	1U
Number of pairs	4 pairs
Installation direction	90°
Communication port support	Ethernet
Contact resistance	20 mOhm
Insulation resistance	>= 500 MOhm
Connector type	U/UTP 6 24 RJ45 connector
Dielectric strength	1000 V
Connections - terminals	IDC
Mounting support	19" rack
Number of matings	>= 750 cycles
Material	ABS + PC + metal (TIA-568A/B) 1.5 mm
Height	44 mm
Width	482 mm
Depth	124 mm
Product weight	1 kg
Targeted region	Asia Pacific

Environment

ambient air temperature for operation	-10...60 °C
standards	ISO/IEC 11801:2011 Ed.2.2 ANSI/TIA-568-C.2 ANSI/TIA-568-C.2 IEC 60603-7-2 AS/NZS 3080:2003 UL 1863
product certifications	UL listed conforming to UL 94 V0

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

RCM conforming to RoHS compliant

ambient air temperature for storage	-20...70 °C
relative humidity	0...93 %