



# [SENTRY]

## LED FLOODLIGHT



### Description

Versatile and designed to suit a wide range of industrial and commercial lighting applications with an efficacy of up to 150lm/W, the [SENTRY] is the ideal replacement for conventional flood lighting across the range of wattages. The [SENTRY] body is built from premium aluminium ensuring maximum strength with minimum weight.


### Key Features

- Wattage Selectable (200W model only)
- Unique angled bracket design to allow easy installation with power tools
- Slim design for easy installation
- Highly efficient achieving up to 150lm/W
- Suitable for a wide range of applications including area, security and commercial lighting
- Asymmetric beam angle for more effective and even light distribution

### Wattage Selection\*

Onboard wattage selection with five selectable wattages.

\*FS-200DT2-W model only



### Flexible Installation

Angled bracket to allow easy installation with power tools.



TEKNIK  
LIGHTING SOLUTIONS


### Wattage Selectable Options

#### FS-200DT2-W Model

**Selectable Wattages** 200W/180W/150W/120W/100W

**Output Levels**


- 100W - 16,300lm
- 120W - 19,440lm
- 150W - 23,625lm
- 180W - 27,360lm
- 200W - 30,000lm



### Technical Specifications

<b>Rated Life</b>	≥50,000 hours	<b>Operating Temperature</b>	-20°C to + 40°C
<b>Body</b>	Aluminium	<b>Input Voltage</b>	90-305 VAC ~ 50/60Hz
<b>Installation</b>	Adjustable bracket	<b>IP Rating</b>	IP65
<b>Beam Angle</b>	Asymmetric T2	<b>IK Rating</b>	IK08
<b>Power Factor</b>	>0.90	<b>Connection</b>	Flex and plug (1.2m)
<b>CRI</b>	>70	<b>Weight</b>	100W: 2.7kg / 150W: 3.2kg / 200W-100W: 3.8kg

### Dimensional Drawing



### Product Data

Part Number	Power	Lumen Output	CCT
FS-100DT2	100W	15,000lm	5000K
FS-150DT2	150W	22,500lm	5000K
FS-200DT2-W	200W-100W	30,000lm-16,300lm	5000K

### Accessories



**Pole Mount**  
FV-BRKT-PM