Shadoweco LED Floodlight

The Pierlite SHADOWECO LED Floodlight is available in 15W, 30W, 50W, 100W and 200W options giving you the general floodlighting ability to illuminate industry & light commercial areas.

- One box solution with colour select and lumen select
- Bonus bracket for corner mounting
- Anti-fog diffuser with breather in-built cable gland

80	IP65	6SDCM	0 - 40°C	Non - Dimmable	3 Years	Symmetric
CRI	Ingress Protection Rating	MacAdam Steps	Operating Temperature	Dimming	Warranty	Beam Distribution

CODE	SYSTEM POWER	EXIT LUMEN	LM/W	CCT	DIMENSIONS	WEIGHT	INRUSH CURRENT	INRUSH CURRENT DURATION
SHADOWECO100BK	100W	10000lm	100lm/W	4000K	L339 x W322 x H98mm	4kg	4A	
SHADOWECO200BK	200W	20000lm	100lm/W	4000K	L414 x W385 x H102mm	6kg		
SHADOWECO30CSLS	30W	2900lm	100lm/W	3000K	L150 x W35 x H177mm	0.56kg	11A	288μs
	30W	3100lm		6500K				
	30W	3300lm		4000K				
	15W	1800lm		3000K				
	15W	1900lm		4000K				
	15W	1800lm		6500K				
SHADOWECO50CS	50W	5290lm	100lm/W	4000K	L180 x W48 x H257mm	1kg	75A	5μs
		4700lm		3000K				
		4860lm		6500K				

Line Drawings

150mm   35mm

177mm

SHADOWECO30CSLS

180mm   48mm

257mm   200mm

SHADOWECO50CS

SHADOWECO100BK

382

306

385

414

102

200W

SHADOWECO200BK

Product Images

SHADOWECO100BK

SHADOWECO30CSLS

SHADOWECO30CSLS

SHADOWECO30CSLS

SHADOWECO30CSLS

SHADOWECO50CS

SHADOWECO50CS

SHADOWECO200BK

SHADOWECO100BK

SHADOWECO200BK