

ORANGE CIRCULAR POWER CABLES

0.6/1kV Orange Circular POWER Cables

Orange Circular Class 2 Bare Copper 4C+E, PVC or XLPE Insulated and PVC 5V90 Sheathed in Compliance to AS/NZS 5000.1



Product Code	Type	Phase Cond. Core		Earth Cond. Core		Avg. Cable Dia. (mm)	Approx. Weight (kg/km)
		Code	Dia. (mm)	Area (mm²)	Dia. (mm)		
1505UA	4C+E	1.5	3.2	1.5	3.2	12.1	235
1502UA	4C+E	2.5	3.6	2.5	3.6	13.3	308
1504UA	4C+E	4	4.6	2.5	3.6	15.5	425
1506UA	4C+E	6	5.1	2.5	3.6	16.7	526
1510UA	4C+E	10	5.8	4	4.6	18.7	742
1516UA	4C+E	16	6.2	6	4.5	20	878
1525UA	4C+E	25	7.8	6	4.5	23.5	1265
1535UA	4C+E	35	8.8	10	5.2	26.0	1700
1550UA	4C+E	50	10.4	16	6.2	30.2	2385
1570UA	4C+E	70	12.2	25	7.8	35.2	3309
1595UA	4C+E	95	13.8	25	7.8	38.8	4282
1520UA	4C+E	120	15.4	35	8.8	43.2	5407
1515UA	4C+E	150	17.4	50	10.4	48.6	6805
1585UA	4C+E	185	19.4	70	12.2	54.3	8477
1524UA	4C+E	240	21.8	95	13.8	60.7	10918
1530UA*	4C+E	300	24.2	120	15.4	67.2	13999

* Made to Order