


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

NOTES:

1. DIAMETER DIMENSION, SHOWN FOR REFERENCE ONLY.
2. DIMENSIONS IN BRACKETS [] ARE ENGLISH.
3. ALL MATERIALS AND COMPONENTS USED MUST MEET THE MATERIAL RESTRICTIONS OF RoHS (EUROPEAN DIRECTIVE 2011/65/EC ON THE RESTRICTION OF HAZARDOUS SUBSTANCES) AS PROPOSED BY THE RoHS TECHNICAL ADAPTATION COMMITTEE.



TECHNICAL SPECIFICATIONS		
MAXIMUM LOSS		SINGLEMODE MAXIMUM LOSS
3.5 dB/KM @ 850nm 1.5 dB/KM @ 1300nm		.40 dB/KM @ 1310nm .30 dB/KM @ 1500nm
BEND RADIUS		
INSTALLATION		LONG TERM
21.8cm [8.6in]		10.9cm [4.3in]
TENSILE LOAD		
INSTALLATION		LONG TERM
2700 N (600 lbf)		1800 N (400 lbf)
TEMPERATURE		
INSTALLATION	OPERATION	STORAGE
-10° C TO +60° C 4° F TO +140° F	-30° C TO +70° C -22° F TO +158° F	-40° C TO +70° C -40° F TO +158° F

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
00	02-13-14	SAT	WMA	TCB	RELEASED TO PRODUCTION	M02055JX-DC

TITLE		12, 24 OUTSIDE PLANT UNARMORED CABLE WITH 12 FIBER SUB-UNITS	
CUSTOMER DRAWING			
ITEM REVISION NAME		M02055JX/00	
DATASET FILE NAME		M02055JX_DC/00A	
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]		PART NO.	
.x ± .xxx ± .010 [0.3]		SEE TABLE	
.xx ± .03 [0.8] ANGLES ±		DRAWING NUMBER:	
THIRD ANGLE PROJECTION		M02055JX-DC	
DRAWN BY	DATE	CHK	SCALE
SAT	02-13-14	WMA	NONE
SHT 1 OF 2			SIZE
			A

